DOMINIQUE IMBERT





### Stripping things back to the essential

Revolutionary in its streamlined simplicity, the Slimfocus is the distillation of a stove and a fireplace. Its minimalist and ergonomic design, compact size (33 cm in diameter), and exceptional performance single it out in the Focus range.

Available as a central, wall or corner model, it blends harmoniously into any space. The Slimfocus is compliant with EU Ecodesign regulations and can be supplied with a conventional or a balanced flue.

#### Versions available

- Suspended Slimfocus, fixed or pivoting, conventional or balanced flue
- Free-standing Slimfocus on a fixed base, conventional or balanced flue
- Wall-mounted Slimfocus

#### **Balanced-flue Slimfocus**

Designed for low-energy homes, the balanced-flue Slimfocus draws its air from outside through the flue. This ensures optimal combustion without disrupting the controlled mechanical ventilation (CMV) system.

The first suspended wood-burning fireplace with sealed combustion that is independent of air in the room, it meets the requirements of the most energy-efficient buildings. Its balanced-flue system avoids the need for holes in the floor or wall to supply air.

32.4 cm diameter

|   | CONVENTIONAL<br>FLUE  | BALANCED<br>FLUE |  |
|---|---|------------------|--|
|   | WOOD  | WOOD             | GAS  |
| Suspended<br>Slimfocus                      | The suspended hearth can rotate up to 360°  |                  |  |
| Free-<br>standing<br>Slimfocus<br>on a base | Nominal heat output: 4.5 kW<br>Efficiency: 82%<br>CO output: 0.1%<br>Particle emission: 30 mg/Nm³       |                  | Natural gas     Maximum heat output: 7 kW     Maximum consumption:     0.723 m3/h                                  |
|   |   |                  | <ul> <li>Propane</li> <li>Maximum heat output: 4.1 kW</li> <li>Maximum consumption:</li> <li>0.144 m3/h</li> </ul> |
| Wall-<br>mounted                            | Nominal heat output:<br>4.5 kW<br>Efficiency: 82%<br>CO output: 0.1%<br>Particle emission:<br>30 mg/Nm³ |                  |  |

- Suspended or on a base Slimfocus: hearthr 96 kg steel flue 35 kg/m
- Suspended Slimfocus pivoting: hearthr 121 kg steel flue 35 kg/m
- Slimfocus on a fixed base (gas): hearthr 107 kg steel flue 35 kg/m
- Wall-mounted Slimfocus: hearthr 89 kg





Suspended, fixed or pivoting, conventional or balanced flue



**M** Wood







Free-standing on a fixed base, conventional or balanced flue









Wall-mounted



**M** Wood













